

# HydraBoost CT™

## High-Powered Concrete and Tile Cleaner and Degreaser/Booster Additive



### HARD SURFACE

pH in solution  
11.0-12.0  
1:32 - 64  
Concrete, Finished  
Concrete, Ceramic,  
Porcelain, & Quarry  
Tile & Grout Floors  
and Surfaces



- » **HydraBoost CT** is a powder, high powered concrete and tile and grout cleaner and degreaser designed to safely and effectively dissolve, break down, dislodge, and emulsify even the grimeiest soils from concrete, finished concrete, and ceramic, porcelain, and quarry tile floors and surfaces.
- » Alkaline cleaning agents and heavy duty surfactants are activated by the power of oxygen to allow the effervescent solution to get into every crack, crevice, and pore. It is the ideal cleaning agent for heavily soiled restaurant kitchen tile floors and other indoor and outdoor surfaces exposed to high levels of grease and oil contamination.
- » **HydraBoost CT** is specifically designed to work in conjunction with high powered hard surface cleaning wands such as the **RX-20** with hard floor attachments, and the **RX-15H** rotary or stationary hard surface cleaning extraction wands. Its powerful formula though, will work with virtually any brush agitation system, automatic floor scrubber, or even a mop and bucket cleaning system for hard surface floors. It can also be used as a pre-treatment on floors being cleaned with an auto-scrubber or in a mop and rinse system.
- » The oxygenated cleaning power also makes it an ideal boosting agent for trashed and neglected carpet that has been exposed to high levels of oxygenated oils and grease. Simply add a couple of ounces to your favorite traffic lane cleaner/preconditioner for the ultimate in cleaning power.

*If for any reason you are not thrilled with the performance of **HydraBoost CT** return it to your distributor and we'll get you a product that does.*



### Directions as a pre-treatment/prespray for tile and grout floors:

1. Read entire label before using. Use only as directed. Always pretest surface with cleaning solution for color-fastness prior to cleaning. Ensure work area is well-ventilated during application. Keep children and pets out of the area during application and drying. **HydraBoost CT** is not recommended for cleaning natural stone floors.
2. This product is ultra-concentrated. For normal soiling, mix 2 ounces of **HydraBoost CT** powder with one gallon of warm or hot water into a professional sprayer. For extreme soiling, mix three to four ounces of powder with a gallon of warm or hot water into a professional sprayer. For application through a Inline Injection Sprayer, mix 12 oz. of powder and fill container with water. Use 4:1 dilution.
3. Apply mixed solution with sprayer evenly and liberally across surface to be cleaned. You can use a pump-up sprayer or a battery powered sprayer. If preferred, you can apply mixed solution with a damp mop, sponge, or other appropriate professional equipment. If using a mop for solution application and surface cleaning, change your mop water often to make sure that soil is not re-deposited.
4. Allow for 5 - 10 minutes of dwell time. For concrete, if stains have been deeply absorbed, allow 15 minutes of dwell time so the solution has time to reach into the concrete pores and crevices and the oxygen activated effervescent solution can dissolve the soiling and lighten discoloration.
5. For best results, agitate and extract cleaning solution using warm or hot water and a rotary agitation hard surface cleaner such as the

**RX-20** with hard floor attachments, or rotary or stationary hard surface cleaning extraction wands For tight spaces or especially sensitive surfaces, use a hard surface cleaning wand, or simply mop to rinse with clean warm or hot water.

6. When area has been rinsed thoroughly. Allow floor to dry.
7. For faster drying, especially in humid environments, consider the use of an axial, centrifugal, or downdraft air mover after cleaning.

### For use as a carpet cleaning solution booster/additive

1. Mix two ounces of **HydraBoost CT** with each gallon of mixed prespray (traffic lane cleaner, preconditioner) solution. This mixture is not recommended for wool carpeting or residential nylon carpets that are being properly maintained.
2. Always pretest surface with boosted cleaning solution for color fast-ness prior to cleaning.
3. Proceed to apply the prespray and continue cleaning in accordance with the directions of the prespray.

See the material safety data sheet at [www.cleanmaster.com](http://www.cleanmaster.com) for safety and regulatory information.



Learn more,  
scan here

Available in: 6.5 Pound Jar; Case of 4 x 6.5 Pound Jar

Part number: 950-782-S, B

11015 47th Ave W, Mukilteo, WA 98275

[www.cleanmaster.com](http://www.cleanmaster.com) • 877.282.2319

**CLEANMaster**  
HydraMaster Cleaning Solutions



**CLEANMaster**