

# Quake HD™

## High Definition Cleaning Carpet Prespray & Traffic Lane Cleaner



- » The perfect carpet prespray for filthy, trashed, and neglected carpeting. Ideal for commercial carpets and rental units.
- » **Quake HD** is a VOC compliant formula that contains the industry exclusive component **Tritanol™** - an integrated blend of specialized polymers, organic synthesizers, and surfactants. With the unprecedented cleaning power and performance of **Tritanol™**, you will experience deep restorative cleaning in high definition.
- » Uncompromising cleaning power in a VOC compliant formula.
- » **Quake HD** is a super-concentrated pre-spray, and is designed to be used at 1 part solution to 8 to 24 parts water depending upon soiling conditions.
- » Ready to use pH of 11.5 – 12.0.
- » It also contains anti-resoiling additives which keep the carpet cleaner longer and does not leave sticky residue.

*If for any reason you are not thrilled with the performance of **Quake HD** return it to your distributor and we'll get you a product that does.*



### Directions:

1. Always pre-test all cleaning solutions in an inconspicuous area for colorfastness prior to application.
2. For increased efficiency, apply **Quake HD** with injection sprayer to take advantage of solution pressure and heat created by your high performance portable extractor or truckmount. You can also use a "pump-up" pressure sprayer, or electric or battery powered sprayer. Apply in even, overlapping patterns.
3. Prespray with 1 part **Quake HD** mixed 24 parts hot water. For extreme soiling, mix **Quake HD** 1 part solution to 8-12 parts water. For standard injection sprayer, mix 1 quart water with 4 quarts of **Quake HD** into 5 quart container.
4. For carpets with high levels of caked-on grease and oil contamination, consider boosting by adding 2 ounces of **GreaseBreaker** with each mixed gallon of **Quake HD**.
5. Extract with a compatible alkaline extraction detergent or acid/neutralizing rinse. For faster cleaning, reduced fatigue, and more effective soil removal, extract with the **RX-20 Rotary Extraction Tool**. In furniture dense environments use the **Evolution** cleaning wand.
6. For faster drying, especially in humid environments, consider the use of an axial, centrifugal, or downdraft air mover after cleaning.

See the material safety data sheet at [www.cleanmaster.com](http://www.cleanmaster.com) for safety and regulatory information.

Learn more, scan here



Available in: 1 Gallon; Case of 4 x 1 Gallon, 5-Gallon Bucket

Part number: 950-127-S, B, C

11015 47th Ave W, Mukilteo, WA 98275

[www.cleanmaster.com](http://www.cleanmaster.com) • 877.282.2319

**CLEANMaster**  
HydraMaster Cleaning Solutions

