

# Release<sup>with</sup> OxyBreak™

## Carpet Prespray and Low Moisture Encapsulation Solution



- » **Release with Oxybreak™ Carpet Pre-spray** enhances the long standing commitment of the **HydraMaster SafeClean** designation. **Release Carpet Pre-spray** contains ingredients that have been identified by industry listing and certification groups as meeting the standard for greener solutions.
- » The cleaning power of **Release Carpet Pre-spray** is increased with the addition of **OxyBreak™** to synergistically enhance cleaning through the power of oxidation. It starts to work on contact to dissolve, dislodge, and encapsulate soil, grease, and oil for easier removal during the extraction process; without the use of any intentionally added solvents, phosphates or other additives which would disqualify its designation as a green cleaning solution.
- » The free rinsing formula contains the **CleanMaster** exclusive **Tritanol™**, which helps the carpet stay cleaner longer and eliminates rapid re-soiling. **Release with Oxybreak™** also works extremely effectively as a low moisture encapsulation carpet cleaning solution when used as directed.
- » The encapsulating polymers surround, bond to, and encapsulate soil allowing it to be removed from the carpet in subsequent vacuuming. The **Oxybreak™** additive makes it an extremely effective encapsulation cleaner on carpets subjected to a high amount of coffee and beverage spills.
- » Release is effective to use and meets the standards of cleaning and care for all synthetic and most wool carpet, including warranted stain resistant carpet. **Release with Oxybreak™** can also be used as a spotting solution to effectively remove many beverage spills and stains, including coffee and tea.



**If for any reason you are not thrilled with the performance of Release with OxyBreak return it to your distributor and we'll get you a product that does.**

### Directions — For use as a carpet prespray

1. Always pre-test all cleaning solutions in an inconspicuous area for colorfastness prior to application.
2. For increased efficiency, apply **Release with Oxybreak™** with an injection sprayer to take advantage of solution pressure and heat created by your high performance portable extractor or truckmount. You can also use a "pump-up" pressure sprayer, or electric or battery powered sprayer. Apply in even overlapping patterns.
3. Pre-spray with 1 part **Release with Oxybreak™** mixed with 24 parts hot water (5.5 ounces of solution with 1 gallon of water). For heavy soiling, mix Release 1 part solution to 12 parts water (12 ounces of solution with 1 gallon of water). For standard injection sprayer, mix 1 quart water with 4 quarts of **Release with Oxybreak™** into 5 quart container.
4. Extract with **CleanMaster RinseFree Liquid Carpet Extraction Detergent**. For faster cleaning, reduced fatigue, and more effective soil removal, extract with the **RX-20 Rotary Extraction Tool**. In furniture dense environments use the **Evolution** cleaning wand.
5. For faster drying, especially in humid environments, consider the use of an axial, centrifugal, or downdraft air mover after cleaning.

### Directions — For use as a low moisture encapsulation carpet cleaning solution

1. Always pre-test all cleaning solutions in an inconspicuous area for colorfastness prior to application.

2. Pre-spray with 1 part **Release with Oxybreak™** mixed with 12 parts hot water (12 ounces of solution with 1 gallon of water). Apply in an even, overlapping pattern with an electric, battery powered, or pump-up sprayer.
3. Agitate the solution into the carpet thoroughly and allow to dry. **Release with Oxybreak™** works effectively with counter rotating cylindrical brush machines, Cimex or other rotary brush machines, bonnet machines, and orbital and oscillating agitation machines.,
4. For faster drying, especially in humid environments, consider the use of an axial, centrifugal, or downdraft air mover after cleaning.
5. Vacuum the carpet thoroughly at the next scheduled interval.

### Directions — For use as a carpet spotter

1. Always pre-test all cleaning solutions in an inconspicuous area for colorfastness prior to application.
2. Mix 1 part **Release with Oxybreak™** mixed with 4 parts water (32 ounces of solution with 1 gallon of water).
3. Saturate spot being treated with solution and allow to dwell for 2 to 5 minutes. Blot with colorfast, absorbent white towel. Extraction not normally required.

See the material safety data sheet at [www.hydramaster.com](http://www.hydramaster.com) for safety and regulatory information.

Learn more, scan here



Available in: 1 Gallon; Case of 4 x 1 Gallon

Part number: 800-405-S, B

11015 47th Ave W, Mukilteo, WA 98275

[www.cleanmaster.com](http://www.cleanmaster.com) • 877.282.2319



**CleanMaster**

