


# ZipDri Encap TS™

## Triple Strength Low Moisture Encapsulation Carpet Cleaning Solution



- » **ZipDri Encap TS** is the only encapsulation cleaner that contains **Tritanol™** - an integrated blend of specialized encapsulating polymers, organic sequestrants, and specialty surfactants.
- » **Tritanol™** helps separate ground in soiling from the carpet fiber, encapsulates soil and holds it in suspension, and makes it easier for subsequent vacuuming to extract more soil than conventional encapsulation cleaners.

*If for any reason you are not thrilled with the performance of ZipDri Encap TS return it to your distributor and we'll get you a product that does.*



### Directions:

#### As a low moisture encapsulation cleaner:

1. Always pre-test all cleaning solutions in an inconspicuous area for colorfastness prior to application.
2. For normal soiling, mix one part **ZipDri Encap TS** with 32-64 parts hot water (2-4 ounces of solution with a gallon of water) into a pump-up, electric, or battery powered pressure sprayer. For heavily soiling, mix one part solution with 16 parts water.
3. Apply the ready-to-use solution as a mist in a consistent, overlapping pattern. Use more solution in heavily soiled areas. For best results, apply with electric or battery powered sprayer.
4. Agitate the solution into the carpet with a counter rotating cylindrical brush machine, triple planetary rotary brush machine, oscillating or orbital agitation machine, or rotary shampoo brush.
5. If using **ZipDri Encap TS** with a bonnet pad system, mix solution 8 ounces to a gallon, and apply to carpet and both sides of bonnet pad. Proceed to clean in normal manner rotating or changing bonnets when the pad stops absorbing soil.
6. Allow the solution to completely dry. To accelerate drying, consider the use of an axial, centrifugal, or downdraft air mover.
7. Vacuum the carpet thoroughly after the carpet dries or at the next scheduled interval.

#### For absorbent bonnet pad cleaning system:

1. If using **ZipDri Encap TS** with a bonnet pad system, mix 8 ounces of solution with a gallon of water into a pump-up, electric, or battery powered pressure sprayer.
2. Apply mixed solution to carpet and both sides of bonnet pad. Proceed to clean in normal manner rotating or changing bonnets when the pad stops absorbing soil.
3. Rinse off dirty bonnet in the mop bucket containing the clean water. Wring pad as dry as possible.
4. Switch to new bonnet as needed and continue process
5. To speed dry the carpet, buff with clean dry bonnets, turning and changing the bonnet often.
6. Allow the solution to completely dry. To accelerate drying, consider the use of an axial, centrifugal, or downdraft air mover.
7. Vacuum the carpet thoroughly after the carpet dries or at the next scheduled interval.

See the material safety data sheet at [www.cleanmaster.com](http://www.cleanmaster.com) for safety and regulatory information.

Learn more, scan here



Available in: 1 Gallon; Case of 4 x 1 Gallon

Part number: 950-152-S, B

11015 47th Ave W, Mukilteo, WA 98275

[www.cleanmaster.com](http://www.cleanmaster.com) • 877.282.2319



**CLEANMaster**

