

The Ultimate®

For Both Wet and Dry Solvent Extraction Cleaning

The Ultimate is the all-in-one cleaning machine, cleaning all fabric types and carpets. This versatile extractor makes it easy to professionally dry clean natural fabric and wet clean synthetics. This unique, patented machine makes every job quick and easy — no more taking down drapes or avoiding certain furniture, fabric panels or oriental carpets. Exclusive features such as adjustable instant heat, quick flush lines, stainless steel tank, solid state circuitry, solvent sensing system and single cord make **The Ultimate** the machine of choice. Call us or visit our website today!

Draperies

Carpets

Ceilings

Upholstery

Fabric Blinds

Office Partitions



"I finally found a lucrative add-on service with virtually no competition - on location dry cleaning of upholstery, draperies and partitions."

- Cleaning contractor

"There is virtually no textile we can't safely and effectively clean with this machine."

- Museum director

"There is still a huge market for solvent/dry cleaning services."

- Industry instructor



4-In-One Tool Kit:

Different heads for cleaning upholstery, drapery and vertical blinds



The Ultimate®

Specifications

Construction	Stainless steel and hexane copolymer for use with solvents and water based detergents
Dimensions	23L x 22H x 10W (inches) / 58.4L x 55.9H x 25.4W (centimeters)
Vacuum	80" (203.2 CM) water lift - 97 CFM
Vacuum Hose	1-1/4" x 10 Ft. (3.175 cm x 3 m) - Vacuum / 1-1/4" x 10 Ft. (3.175 cm x 3 m) - Exhaust
Pressure Line	1/8" x 10 Ft. (.3175 cm x 3 m) with all brass disconnects
Heat Exchanger	Stainless Steel coil, instant heat transfer
Circuit Board	Solid-state technology monitoring system controls heating operation (sensing within 1° F {,56° C}) protected by dual fail-safe system
Sensing Systems	Solid-state circuitry
Electrical System	25 Ft. (7.62 m) 12/3 cord; available in 120 & 240 V, 50/60 cycle (Ultimate-230-CE)
Weight	46 lbs - 20.87 kg
Solvent Sensing Probe	Determines whether there is solvent or water-base cleaner in holding tank. (Patented) Unique fail safe system automatically prevents solvent from heating above 122° F (51.67° C) regardless of heat setting
Pump	Centrifugal type 40 P.S.I., carbon and ceramic seals and brass head, slide-mount and compression fittings for quick removal and servicing

Other Features & Specifications

