


# FastBreak HD™

High Definition Cleaning Carpet Prespray & Traffic Lane Cleaner



- » **Fast Break HD** is a VOC compliant formula that contains the industry exclusive component **Tritanol™** - an integrated blend of specialized polymers, organic synthesizers, and surfactants. With the unprecedented cleaning power and performance of **Tritanol™**, you will experience deep restorative cleaning in high definition. It just works better!
- » **Fast Break HD** is a special blend of surfactants, and is packed with soil busting, grease cutting and dissolving ingredients with an unbeatable cleaning power that out-cleans competitive products – at a safe pH of 9.5.
- » Concentrated 32-64:1 dilution rate, using 2-4 oz. per gallon of water
- » Highly effective on all synthetic fibers and commercial wool carpets

*If for any reason you are not thrilled with the performance of **FastBreak HD** return it to your distributor and we'll get you a product that does.*



## Directions:

1. Always pre-test all cleaning solutions in an inconspicuous area for colorfastness prior to application.
2. For increased efficiency, apply **FastBreak HD** with an injection sprayer to take advantage of solution pressure and heat created by your high-performance portable extractor or truckmount. You can also use a “pump-up” pressure sprayer, or electric or battery powered sprayer. Apply in even, overlapping patterns.
3. For medium-to-heavy soiling, mix 1 part solution with 32 parts water (4 ounces to 1 gallon/.12 liters to 3.785 liters). For lighter soiling, mix 1 part solution with 64 parts water (2 ounces to 1 gallon/.06 liters to 3.785 liters) For standard injection sprayer, mix 1 quart solution with 4 quarts of water into 5 quart container.
4. For carpets with high levels of caked-on grease and oil contamination, consider boosting by adding 2 ounces of **Grease-Breaker** with each mixed gallon of **Fast Break HD**.
5. Extract with a compatible alkaline extraction detergent or acid/neutralizing rinse. For faster cleaning, reduced fatigue, and more effective soil removal, extract with the **RX-20 Rotary Extraction Tool**. In furniture dense environments, use the **Evolution** cleaning wand.
6. For faster drying, especially in humid environments, consider the use of an axial, centrifugal, or downdraft air mover after cleaning.

See the material safety data sheet at [www.cleanmaster.com](http://www.cleanmaster.com) for safety and regulatory information.

Learn more,  
scan here



Available in: 1 Gallon; Case of 4 x 1 gallon; 5 gallon pail

Part number: 950-132-S, B, C

11015 47th Ave W, Mukilteo, WA 98275

[www.cleanmaster.com](http://www.cleanmaster.com) • 877.282.2319

**CLEANMaster**  
HydraMaster Cleaning Solutions



**CLEANMaster**