

# HydraSolv™

## High Powered Tile and Grout Cleaner and Degreaser



- » **HydraSolv** is a high powered cleaning and degreasing agent specifically formulated for ceramic, porcelain, and quarry tile floors and their grout lines. It is used as a prespray/pretreatment on tile and grout to loosen, breakdown, dissolve, and emulsify even the grimeiest of soils.
- » It can be used on residential or commercial tile floors and other hard surfaces, indoors and outdoors.
- » **HydraSolv** is formulated to work in conjunction with the **RX-20 Rotary Extraction Tool** with hard surface attachments, the **RX-15H Rotary Hard Surface Tool**, or any high pressure wand compatible with hard surface floors. It can also be used as a pre-treatment on floors being cleaned with an auto-scrubber or in a mop and rinse system.
- » **HydraSolv** is also an excellent cleaner for hard surfaces that have been exposed to fire and smoke as it effectively removes soot.

*If for any reason you are not thrilled with the performance of **HydraSolv** return it to your distributor and we'll get you a product that does.*



### Directions as a pre-treatment/prespray for tile and grout floors:

1. Always pre-test all cleaning solutions in an inconspicuous area for colorfastness prior to application.
2. For increased efficiency, apply **HydraSolv** with injection sprayer to take advantage of solution pressure and heat created by your high performance portable extractor or truckmount. You can also use a "pump-up" pressure sprayer, or electric or battery powered sprayer. Apply in even overlapping patterns.
3. For deep restorative cleaning, prespray with 1 part **HydraSolv** mixed with 4 parts hot water (32 ounces of solution with one gallon of water). For maintenance cleaning, mix **HydraSolv** 1 part solution to 16-32 parts water. For standard injection sprayer, mix one quart water with four quarts of Quake into 5 quart container.
4. Allow solution to dwell 2-5 minutes. Extra agitation with brushes compatible with tile and grout may be helpful.
5. Extract the solution utilizing the **RX-20 Rotary Extraction Tool** with hard surface attachments, the **RX15-H Rotary Hard Surface Tool**, or any high pressure wand compatible with hard surface floors.
6. For faster drying, especially in humid environments, consider the use of an axial, centrifugal, or downdraft air mover after cleaning.

### Directions as a general hard surface degreaser and soot remover:

1. Always pre-test all cleaning solutions in an inconspicuous area for colorfastness prior to application.
2. For increased efficiency, apply **HydraSolv** with injection sprayer to take advantage of solution pressure and heat created by your high performance portable extractor or truckmount. You can also use a "pump-up" pressure sprayer, or electric or battery powered sprayer. Apply in even overlapping patterns.
3. Prespray with 1 part **HydraSolv** mixed with 8 parts hot water (16 ounces of solution with one gallon of water).
4. Allow solution to dwell 2-5 minutes. Extra agitation with brushes compatible with surface may be helpful.
5. Extract or pressure wash depending upon surface being cleaned.
6. For faster drying, especially in humid environments, consider the use of an axial, centrifugal, or downdraft air mover after cleaning.

See the material safety data sheet at [www.hydramaster.com](http://www.hydramaster.com) for safety and regulatory information.

Learn more, scan here



Available in: 1 Gallon; Case of 4 x 1 Gallon

Part number: 950-165-S, B

11015 47th Ave W, Mukilteo, WA 98275

[www.cleanmaster.com](http://www.cleanmaster.com) • 877.282.2319

**CLEANMaster**  
HydraMaster Cleaning Solutions

