

Ultra-Concentrated Liquid Carpet Cleaning Extraction Detergent



**HydraClean** completes the maximum soil removal, minimum residue cleaning process of the professional hot water extraction cleaning, virtually eliminating re-soiling issues common to many carpet cleaning solutions. HydraClean allows you to use your solution pressure to remove soil that is deeply imbedded into the carpet pile with emulsifiers that hold the soil in suspension for easy removal.

**HydraMaster**.



If for any reason you are not thrilled with the performance of HydraClean return it to your distributor and we'll get you a product that does.

Five U.S. Gallons (18.92 liters)

HydraMaster HydraClean is a liquid ultra-concentrated blend of solvents, builders and emulsifiers designed to tackle the challenges of today's professional carpet cleaner. Used in conjunction with your favorite **HydraMaster** prespray, HydraClean completes the maximum soil removal, minimum residue cleaning process of the professional hot water extraction cleaning, virtually eliminating re-soiling issues common to many carpet cleaning solutions. HydraClean allows you to use your solution pressure to remove soil that is deeply imbedded into the carpet pile with emulsifiers that hold the soil in suspension for easy removal. HydraClean is safe to use on all colorfast synthetic carpet, warranted residential stain resistant carpets, and leaves a refreshing scent that says clean without overpowering. HydraClean is a VOC compliant formula that contains the industry exclusive component **Tritanol**<sup>™</sup> - an integrated blend of specialized encapsulating polymers, organic sequestrants, and surfactants. With the unprecedented cleaning power and performance of **Tritanol**<sup>™</sup>, you will experience deep restorative cleaning in high definition. It just works better! A gallon of HydraClean is so concentrated it will make 320 gallons, or more, of ready-to-use cleaning solution and will clean up to 35,000 square feet of carpet.

## Directions:

- Always pre-test all cleaning solutions in an inconspicuous area for colorfastness prior to
- Select and apply the appropriate **HydraMaster** preconditioning pre-spray solution first.
- For portable units; mix **HydraClean** at a rate of 2 oz. per 5 gallons of water. In truckmount units; mix 1 guart of HydraClean with 5 gallons of water to make a concentrated solution. Set your solution flow meter from 2 to 3 aph.
- Extract carpet thoroughly making sure to slow down in heavy soiled areas and use a dry stroke to dry the carpet faster and return it to service quicker. For faster cleaning, reduced fatigue, and more effective soil removal, extract with the RX-20 Rotary Extraction **Tool**. In furniture dense environments use the **Evolution** cleaning wand.
- For faster drying, especially in humid environments. consider the use of an axial, centrifugal, or downdraft air mover after cleaning.

Contents: 2-butoxyethanol (111-76-2), sodium tripolyphosphate (7758-29-4), tetrapotassium pyrophosphate (7320-34-5), proprietary surfactants, polymers, and fragrance.

## Instrucciones:

- . Siempre antes de la prueba todas las soluciones de limpieza en un área discreta de durabilidad antes de la aplicación
- 2. Seleccionar y aplicar el precondicionamiento HydraMaster adecuada formación agraria solución en primer lugar.
- Para unidades portátiles mezclar HydraClean a un ritmo de 2 oz. por cada 5 galones de agua. En truckmount unidades - mezclar 1 cuarto de galón de HydraClean con 5 galones de agua para hacer una solución concentrada. Configurar el medidor de caudal de solución de 2 a 3 aph.
- Extracto alfombra completamente asegurándose de que para frenar el fuerte en las superficies manchadas y utilizar un seco golpe para secar la alfombra más rápido y vuelva a ponerlo en servicio más rápido. Para una mayor limpieza, reducción de la fatiga, y más eficaz del suelo extracción, extracto con el RX-20 Rotary Herramienta de extracción. Muebles en entornos de alta densidad uso la evolución limpieza varita.
- 5. Para un secado más rápido, especialmente en ambientes húmedos, considere el uso de un axial. centrífugos, aire descendente o transportador después de realizar la limpieza.

GHS U.S. - CLASSIFICATION: WAR

Skin corrosion/irritation Category 3 Serious eye damage/eye irritation Category 2

## PRECAUTIONARY STATEMENTS (GHS-US)

May be harmful if swallowed. May cause mild skin irritation. Causes eve irritation.

The product is classified and labeled according to the Globally Harmonized System (GHS)

If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Wash skin and contaminated clothing thoroughly after handling. Do not eat, drink or smoke when using this product. Use personal protective equipment as

■ IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel

IF ON SKIN: Wash with plenty of soap and water.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing. Dispose of contents/container in accordance with local/regional/national/ international regulations.

CLASSIFICATION SYSTEM: NFPA/HMIS Definitions: 0-Least, 1-Slight. 2-Moderate, 3-High, 4-Extreme.

■ NFPA RATINGS (SCALE 0-4): Health = 1, Fire = 0, Reactivity = 0 HMIS RATINGS (SCALE 0-5): Health = 1, Fire = 0, Reactivity = 0



See Safety Data Sheet (SDS): scan here or visit www.hvdramaster.com/sds for additional safety and regulatory information.

Part # 950-110-C Art 950-110-C R2

HydraMaster 11015 47th Avenue West Mukilteo, WA 98275 425.775.7272



www.HydraMaster.com