



with
TRITANOL
1+1=3

PRE-SPRAY

RTU pH 11.5 - 12.0
1:8-24
Commercial
Synthetic Carpets
& Neglected
Residential Carpets

Quake HD

High Definition Cleaning Carpet Prespray & Traffic Lane Cleaner

Uncompromising cleaning power is now available in a VOC compliant formula with Quake HD. Quake HD is a VOC compliant formula that contains the industry exclusive component Tritanol™ - an integrated blend of specialized polymers, organic sequestrants, and surfactants. With the unprecedented cleaning power and performance of Tritanol™, you will experience deep restorative cleaning in high definition.



If for any reason you are not thrilled with the performance of Quake HD return it to your distributor and we'll get you a product that does.



Important notice to purchaser: The manufacturer and seller warrant that the chemical contained herein conforms to its standard specifications. Seller's and manufacturer's liability for any and all losses or damages resulting from any cause whatsoever shall in no event exceed the purchase price of this product, with respect to which losses or damages are claimed. Before using, user shall determine the suitability of the product for the intended use and user assumes all risk and liability whatsoever in connection therewith. The product contains oxidizers and may alter or remove the original color of the carpet it is being applied to. Use only as a last resort and with the customer's permission and understanding of this risk.

Directions:

1. Always pre-test all cleaning solutions in an inconspicuous area for colorfastness prior to application.
2. For increased efficiency, apply **Quake HD** with injection sprayer to take advantage of solution pressure and heat created by your high performance portable extractor or truckmount. You can also use a "pump-up" pressure sprayer, or electric or battery powered sprayer. Apply in even overlapping patterns.
3. Prespray with 1 part **Quake HD** mixed with 24 parts hot water. For extreme soiling, mix **Quake HD** 1 part solution to 8-12 parts water. For standard injection sprayer, mix one quart water with four quarts of **Quake HD** into 5 quart container.
4. For carpets with high levels of caked-on grease and oil contamination, consider boosting by adding two ounces of **GreaseBreaker** with each mixed gallon of **Quake HD**.
5. Extract with a compatible alkaline extraction detergent or acid/neutralizing rinse. For faster cleaning, reduced fatigue, and more effective soil removal, extract with the **RX-20 Rotary Extraction Tool**. In furniture dense environments use the **Evolution cleaning wand**.
6. For faster drying, especially in humid environments, consider the use of an axial, centrifugal, or downdraft air mover after cleaning.

Instrucciones:

1. Siempre antes de probar todas las soluciones de limpieza en un área poco visible la estabilidad del color antes de la aplicación.
2. Para una mayor eficacia, aplicar **Quake HD** con el rociador de la inyección para tomar ventaja de la presión de la solución y el calor creado por su alto rendimiento extractor portátil o Truckmount. También puede utilizar una "bomba-up" pulverizador o rociador potencia eléctrica o la batería. Aplicar en la superposición de patrones, incluso.
3. Prespray con 1 parte de mixta **Quake HD** 24 partes de agua caliente. En caso de suciedad extrema, mezcle una solución de **Quake HD** parte a 8.12 partes de agua. Para el pulverizador de inyección estándar, mezclar un litro de agua con cuatro cuartos de **Quake HD** en un recipiente de 5 cuartos.
4. Para las alfombras con altos niveles de apelmazar-en la grasa y la contaminación por petróleo, considere aumentar mediante la adición de dos onzas de **GreaseBreaker** con cada galón de mezcla de **Quake HD**.
5. Se extrae con un detergente compatible extracción alcalina o ácida / neutralizar enjuague. Para una limpieza más rápida, reducción de la fatiga y la eliminación de la suciedad más efectivo, el extracto con el **RX-20 Herramienta de extracción de Rotary**. En muebles de ambientes densos utilizar la varita de limpieza **Evolución**.
6. Para un secado más rápido, especialmente en ambientes húmedos, considerar el uso de un motor axial, aire centrifugo, o corriente descendente después de la limpieza.

GH S U.S. – CLASSIFICATION: WARNING

Harmful if swallowed. Causes skin irritation. Causes serious eye irritation.

PRECAUTIONARY STATEMENTS (GHS-US)

- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children. Read label before use.
- Wash skin and contaminated clothing thoroughly after handling.
- Do not eat, drink or smoke when using this product.
- Wear suitable protective gloves/protective clothing/eye protection/face protection.
- IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
- IF ON SKIN: Wash with plenty of soap and water.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- If skin irritation occurs: Get medical advice/attention.
- If eye irritation persists: Get medical advice/attention.
- Dispose of contents/container in accordance with local/regional/national/international regulations.

OSHA HAZARDS: Target Organ Effect (Glycol Ether DPM)

TARGET ORGANS: Kidney, Liver, Nerves (Glycol Ether DPM).

CLASSIFICATION SYSTEM: NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme.

NFPA RATINGS (SCALE 0-4): Health = 1, Fire = 0, Reactivity = 0

HMIS RATINGS (SCALE 0-5): Health = 1, Fire = 0, Reactivity = 0



See Safety Data Sheet (SDS): scan here or visit www.hydramaster.com/sds for additional safety and regulatory information.

Lot:

Part # 950-127-A Art 950-127-S R2



HydraMaster

11015 47th Avenue West

Mukilteo, WA 98275

425.775.7272



8 10149 01130 6

Net Contents: One U.S. Quart (.9463 liters)