FastBreak



Ultra Concentrated Carpet Pre-Spray

Quickly breaks down surface tension to allow detergents and rinse agents to clean deep down.



Available in: 1 Gallon; Case of 4 x 1 gallon; 5 gallon pail Part # 950-130

Product cannot ship via air freight This item can not ship to the following states: CA, CT, DC, DE, IN, IL, MA, MD, ME, MI, NH, NJ, NY, OH, PA, RI, UT, VA, VT FastBreak is a special blend of surfactants, and is packed with soil busting, grease cutting and dissolving ingredients with an unbeatable cleaning power that outcleans competitive products.

- FastBreak is an ultra-concentrated blend (32-64:1) of solvents, surfactants and builders that will make fast work of even the toughest traffic lanes. FastBreak is a special blend of surfactants, and is packed with soil busting, grease cutting and dissolving ingredients with an unbeatable cleaning power that out-cleans competitive products – at a safe pH of 9.5.
- · Concentrated 32:1 dilution rate, using 4 oz. per gallon of water
- · Highly effective on nylon and olefin fibers
- FastBreak may be used with Grease Breaker for oily soils or other difficult carpet restorations

Mixing Directions:

- 1. Always pre-test all cleaning solutions in an inconspicuous area for colorfastness prior to application.
- 2. For increased efficiency, apply FastBreak with an injection sprayer to take advantage of solution pressure and heat created by your high performance portable extractor or truckmount. You can also use a "pump-up" pressure sprayer, or electric or battery powered sprayer. Apply in even overlapping patterns.
- 3. For medium to heavy soiling, mix one part solution with 32 parts water (four ounces to a gallon/ .12 liters to 3.785 liters). For lighter soiling mix one part solution with 64 parts water (2 ounces to a gallon/.06 liters to 3.785 liters) For standard injection sprayer, mix one quart solution with four quarts of water into five quart container.
- 4. For carpets with high levels of caked-on grease and oil contamination, consider boosting by adding two ounces of GreaseBreaker with each mixed gallon of FastBreak.
- 5. Extract with a compatible alkaline extraction detergent or acid/neutralizing rinse. For faster cleaning, reduced fatigue, and more effective soil removal, extract with the RX-20 Rotary Extraction Tool. In furniture dense environments use the Evolution cleaning wand.
- For faster drying, especially in humid environments, consider the use of an axial, centrifugal, or downdraft air mover after cleaning.





www.hydramaster.com | 800.426.1301 | 425.775.7272 sales@hydramaster.com