

HydraSolv



HARD SURFACE

RTU pH 11.5-12.0

1:4 - 64

Ceramic, Porcelain,
Quarry Tile & Grout
Floors & Surfaces

High Powered Tile and Grout Cleaner and Degreaser

HydraSolv™ is a high powered cleaning and degreasing agent specifically formulated for ceramic, porcelain, and quarry tile floors and their grout lines.

HydraSolv is used as a pre-spray or pretreatment on tile and grout to loosen, breakdown, dissolve, and emulsify even the grimeiest of soils.

- High powered cleaning and degreasing agent specifically formulated for ceramic, porcelain, and quarry tile floors and their grout lines.
- It can be used on residential or commercial tile floors and other hard surfaces, indoors and outdoors.
- HydraSolv is formulated to be used as a pre-treatment on floors being cleaned with an auto-scrubber or in a mop and rinse system.
- HydraSolv is also an excellent cleaner for hard surfaces that have been exposed to fire and smoke as it effectively removes soot.

Directions:

Please read the full label directions before cleaning.

As a pre-treatment/prespray for tile and grout floors:

1. Pre-test all cleaning solutions in an inconspicuous area for colorfastness prior to application.
2. For increased efficiency, apply HydraSolv with injection sprayer to take advantage of solution pressure and heat created by your high performance portable extractor or truckmount. You can also use a "pump-up" pressure sprayer, or electric or battery powered sprayer. Apply in even overlapping patterns.
3. For deep restorative cleaning, prespray with 1 part HydraSolv mixed with 4 parts hot water (32 ounces of solution with one gallon of water). For maintenance cleaning, mix HydraSolv 1 part solution to 16-32 parts water. For standard injection sprayer, mix one quart water with four quarts of Quake into 5 quart container.
4. Allow solution to dwell 2-5 minutes. Extra agitation with brushes compatible with tile and grout may be helpful.
5. Extract the solution utilizing the RX-20 Rotary Extraction Tool with hard surface attachments, the RX15-H Rotary Hard Surface Tool, or any high pressure wand compatible with hard surface floors.
6. For faster drying, consider the use of an axial, centrifugal, or downdraft air mover after cleaning.



Available in: 1 Gallon; Case of 4 x 1 Gallon
Part # 950-165

HydraMaster
We've Got Your Back

www.hydramaster.com | 800.426.1301 | 425.775.7272
sales@hydramaster.com

