

HydraStone



HARD SURFACE

RTU pH 10.6-11.0

1:8 - 32

Marble, granite, limestone, travertine, slate & sandstone, ceramic, porcelain and quarry tile & grout

Heavy Duty Stone and Tile Cleaning Solution

HydraStone Heavy Duty Stone, Tile and Grout Cleaning solution is specially formulated for the heavy duty cleaning of natural stone floors and surfaces, as well as tile and grout floors and walls.

HydraStone was specifically made to safely and effectively clean stone and tile surfaces, unlike most hard surface cleaners that contain water conditioning agents and harsh solvents that can actually etch and damage fine stone.



- HydraStone is designed to deep clean and restoratively clean marble, granite, limestone, travertine, slate & sandstone as well as ceramic, porcelain and quarry tile & grout. It also works to effectively dissolve and emulsify stubborn soils on masonry and concrete.
- HydraStone is designed to be applied as a prespray/pretreatment spray to loosen, dissolve, break down and emulsify built-up soiling, and to assist in stain removal. It is the ideal stone and tile cleaner for stone and tile surfaces that have been affected by smoke and soot damage following a fire or furnace puff-back.

Directions:

Please read the full label directions before cleaning.

1. Sweep or vacuum floors prior to deep cleaning to remove particulate soils. An untreated microfiber dust mop works well for this.
2. For normal soiling, Mix 1 part HydraStone with 16 parts water into sprayer (8 ounces of solution/gallon of water). For heavy soiling, mix 1 part HydraStone with 8 parts water 16 ounces of solution/gallon of water). For maintenance cleaning of counter tops and other surfaces, mix 1 part HydraStone with 32 parts water (4oz of solution/gallon of water)
3. Apply with sprayer or mop
4. Allow several minutes of dwell time but do not allow solution to dry.
5. Grout lines may need to be agitated with a grout brush.
6. For best results, agitate and extract cleaning solution using high pressure warm or hot water from a RX20 with a hard surface attachment, hard surface rotary extraction tool or high pressure hard surface wand. Your portable or Truckmounted extractor should maintain a minimum of 800 psi and a maximum of 1200 psi. For more sensitive surfaces, consider using a hard surface wand or simply mop with clean water and rinse.
7. For faster drying, especially in humid environments, consider the use of an axial, centrifugal, or downdraft air mover after cleaning.
8. After the floor has dried, consider the need for application of HydraSeal to protect the surface.

Available in: 1 Gallon; Case of 4 x 1 Gallon
Part # 950-777

HydraMaster
We've Got Your Back



www.hydrmaster.com | 800.426.1301 | 425.775.7272
sales@hydrmaster.com