

HydraVitalize



HARD SURFACE

RTU pH 2.0-3.0

1:4 - 8

Acid cleaning of tile & grout, granite, slate & sandstone

Acid Stone, Tile and Grout Revitalizing & Renewing Cleaning Solution

HydraVitalize is used to renew and restore stone, tile and grout that has not responded effectively to other types of cleaning, or that has been exposed to a build-up of hard water spots, deposits, grout haze, soap scum, pet urine deposits, rust, and efflorescence. The acid cleaning action revitalizes and renews the appearance of ceramic, porcelain and quarry tile, as well as grout, granite, slate and sandstone.

HydraVitalize breaks down and removes scale and soap scum, removes the white haze caused by efflorescence and removes the oxidized and imbedded soil from porous grout.



- The acid cleaning action revitalizes and renews the appearance of ceramic, porcelain and quarry tile, as well as grout, granite, slate and sandstone.
- It uses a safer and milder proprietary acid than conventional acids so it emits fewer vapors and requires fewer precautions.
- This acid-based cleaner will etch or damage most marble, limestone and travertine surfaces, so only use on recommended surfaces and always pre-test in an inconspicuous area first.

Directions:

Read entire label before using. Use only as directed. Before cleaning, sure all surfaces are swept or vacuumed to remove loose debris.

Acid Cleaning of tile and grout: When cleaning with acid solutions, take special precautions to prevent splashes or spills onto metal surfaces, particularly stainless steel appliances.

1. Apply HydraVitalize. For normal soiling, mix 1 part solution with five parts water. For heavy soiling, mix 1 part solution with 1 part water. For routine maintenance, mix 1 part solution with 10 parts water.
2. Apply solution generously to floor with sprayer or mop.
3. Grout lines may need to be agitated with a grout brush.
4. For best results, agitate and extract cleaning solution using high pressure warm or hot water from a RX20 with a hard surface attachment, hard surface rotary extraction tool or high pressure hard surface wand. Your portable or Truckmounted extractor should maintain a minimum of 800 psi and a maximum of 1200 psi. For more sensitive surfaces, consider using a hard surface wand or simply mop with clean water and rinse. Specialty hand-held hard surface pressure cleaning tools will be very helpful when cleaning countertops, walls, along edges, and in tight places.
5. For grout, it is important to neutralize the cleaning solution residue. Mix one part HydraStone or HydraSolv with 32 parts water and apply to grout. Allow several minutes of dwell time and then rinse with water.
6. For faster drying, especially in humid environments, consider the use of an axial, centrifugal, or downdraft air mover after cleaning.
7. After the floor has dried, consider the need for application of HydraSeal to grout surfaces to protect the grout.

Available in: 1 Gallon; Case of 4 x 1 Gallon
Part # 950-792

Product cannot ship via air freight



HydraMaster
We've Got Your Back



www.hydrmaster.com | 800.426.1301 | 425.775.7272
sales@hydrmaster.com