

SAFETY DATA SHEET

FABRIC MASTER HD

SECTION 1- PRODUCT IDENTIFICATION

PRODUCT NAME : FABRIC MASTER HD
SYNONYMS : Product is a mixture: No synonyms are available.
PRODUCT USE : Moderately Alkaline Material
SUPPLIER : HYDRAMASTER CORP.
SUPPLIER'S ADDRESS : 11015 47TH AVE W, MUKILTEO, WA 98275
(425) 776-7272
EMERGENCY RESPONSE PHONE : PERS: 1-800-633-8253

SECTION 2 – HAZARD IDENTIFICATION

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

GHS U.S. – CLASSIFICATION : H302 Harmful if swallowed.
: H315 Causes skin irritation
: H319 Causes serious eye irritation

LABEL ELEMENTS : **GHS – US HAZARD PICTOGRAMS** The product is classified and labeled according to the Globally Harmonized System (GHS).

HAZARD PICTOGRAMS :



SIGNAL WORD : WARNING

HAZARD STATEMENTS (GHS-US) : Not established

: H302 Harmful if swallowed.
: H315 Causes skin irritation.
: H319 Causes serious eye irritation.

PRECAUTIONARY STATEMENTS (GHS-US) : P101 If medical advice is needed, have product container or label at hand.

: P102 Keep out of reach of children.
: P103 Read label before use.
: P264 Wash skin and contaminated clothing thoroughly after handling.
: P270 Do not eat, drink or smoke when using this product.
: P280 Wear suitable protective gloves/protective clothing/eye protection/face protection.
: P301+P312 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
: P302+P352 : IF ON SKIN: Wash with plenty of soap and water.
: P305+351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
: P332+P313 If skin irritation occurs: Get medical advice/attention.
: P337+P313 If eye irritation persists: Get medical advice/attention.
: P501 Dispose of contents/container in accordance with local/regional/national/international regulations

OSHA HAZARDS : Not applicable

TARGET ORGANS : Not applicable

CLASSIFICATION SYSTEM : NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme.

NFPA RATINGS (SCALE 0-4) : Health = 2, Fire = 0, Reactivity = 0

HMIS RATINGS (SCALE 0-5) : Health = 2, Fire = 0, Reactivity = 0

SAFETY DATA SHEET

FABRIC MASTER HD

SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS

CHEMICAL CHARACTERISTIC : Mixtures
DESCRIPTION : Mixture of the substances listed below with nonhazardous additions.

COMPONENT	PERCENT	CAS #	EINECS #	GHS CLASSIFICATION
Diethylene Glycol Monobutyl Ether	5-10	112-34-5	203-961-6	Eye Irrit: Cat 2B
Sodium Octane Sulfonate	1-5	5324-84-5	226-195-4	Skin Irrit Cat 2, Eye Irrit Cat 2A STOT SE Cat 3
Alcohol Ethoxylate	1-5	68439-46-3	Not Found	Eye Irrit Cat 2B
Sodium Thiosulfate	1-5	7772-98-7	231-867-5	Eye Irrit Cat 2B

Irrit. = Irritation, Corr. = Corrosion, Cat. = Category, Dam = Damage, Tox = Toxic, STOT SE = Single Target Organ Toxicity
 Single exposure.

SECTION 4 – FIRST AID MEASURES

DESCRIPTION OF FIRST AID MEASURES

GENERAL : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice. Show the label where possible.

EYE CONTACT : Immediately flush eyes with water for at least 15 minutes. Hold eyelids open to ensure adequate flushing. Get immediate medical attention.

SKIN CONTACT : Remove contaminated clothing and shoes. Wash affected skin area with soap and water. Delayed skin damage is possible if product is not completely washed off. Get immediate medical attention.

SWALLOWING (INGESTION) : If ingested, dilute swallowed material by drinking water. **DO NOT INDUCE VOMITING.** If vomiting occurs spontaneously, keep airway clear. Give more water when vomiting stops. Never give anything by mouth to an unconscious person. Get immediate medical attention.

INHALATION : Remove to fresh air. Get immediate medical attention.

OTHER INSTRUCTIONS : Rescue personnel must wear appropriate protective equipment during removal of victims from contaminated areas. Treat symptomatically and supportively.

SECTION 5 – FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA : Dry chemical, foam, water or carbon dioxide.

SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE FIGHTERS : In the event of a fire, wear a NIOSH (USA) or CEN (EU) approved, positive pressure, self-contained breathing apparatus (SCUBA) and full protective clothing. Evacuate all non-essential personnel from the danger area.

UNUSUAL FIRE AND EXPLOSION HAZARDS : No further relevant information is available.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT & EMERGENCY PROCEDURES : Restrict access to keep out unauthorized or unprotected personnel. Wear protective equipment. Avoid inhalation and direct contact.

ENVIRONMENTAL PROCEDURES : Keep spilled material away from sewage/drainage systems and waterways.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEAN-UP : All clean-up personnel must be properly trained. Confine the spill and remove incompatible materials and ignition sources. Ensure adequate ventilation. Secure the source of the leak if conditions are safe. Neutralize spill and collect using an appropriate absorbent material such as clay or vermiculite. Place waste in an

SAFETY DATA SHEET

FABRIC MASTER HD

appropriate container for disposal. Use care during clean-up to avoid exposure to the material and injury from broken containers.

SECTION 7 – HANDLING AND STORAGE

- PRECAUTIONS FOR SAFE HANDLING** : Use with adequate ventilation. Wear proper protective equipment. Do not mix with water or acids without proper dilution and agitation to prevent a potentially violent reaction.
- CONDITIONS FOR SAFE STORAGE** : Store in closed, properly labeled containers. Protect containers from heat, physical damage, ignition sources and incompatible materials. Have emergency equipment for fires and spills readily available.



SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

- TLV (THRESHOLD LIMIT VALUE)** : The TLV in section in section III is the ACGIH/TLV-TWA (threshold limit value/time weighted average concentration for an eight hour work day). The STEL is the short term exposure limit and the (Ceil) is the ceiling limit.

COMPONENT	OSHA PEL – TWA	ACGIH – TLV	ACGIH – STEL
Diethylene Glycol Monobutyl Ether	Not Established	Not Established	Not Established
Sodium Octane Sulfonate	Not Established	Not Established	Not Established
Alcohol Ethoxylate	Not Established	Not Established	Not Established
Sodium Thiosulfate	Not Established	Not Established	Not Established

- EYE PROTECTION** : Wear chemical splash goggles or face shield.
- SKIN PROTECTION** : Minimize contact with product. Wear chemical resistant coveralls, boots, gloves, apron and/or suitable long-sleeved clothing.
- RESPIRATORY PROTECTION** : In case of brief exposure use respiratory filter device. In case of intensive or longer exposure, use respiratory protective device that is independent of circulating air.
- VENTILATION** : Ensure adequate ventilation.
- ADDITIONAL MEASURES** : Emergency eyewash and safety shower facilities should be available in the immediate work area.
- REQUIRED WORK/HYGIENE** : Wash hands thoroughly after handling. Keep away from all food stuffs, beverages and feed. Do not eat, drink or smoke in work area.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

- APPEARANCE** : Clear light amber liquid with mild odor.
- ODOR** : Slight Odor.
- ODOR THRESHOLD** : Not available
- PH** : 11.25 ± 0.25
- MELTING POINT/FREEZING POINT** : Not available
- BOILING POINT** :
- FLASH POINT** : > 200° F.
- EVAPORATION RATE** : Not available
- FLAMMABILITY** : Non flammable-Non combustible
- LOWER FLAMMABILITY LIMIT** : Not available
- UPPER FLAMMABILITY LIMIT** : Not available
- VAPOR PRESSURE** : Not available

SAFETY DATA SHEET

FABRIC MASTER HD

VAPOR DENSITY (AIR=1) : Not available
RELATIVE DENSITY : 1.02
SOLUBILITY IN WATER : Soluble in water
PARTITION COEFFICIENT n-
OCTANOL/WATER : Not available
AUTOIGNITION TEMPERATURE : Not available
DECOMPOSITION
TEMPERATURE : Not available

SECTION 10 – STABILITY AND REACTIVITY

STABILITY : Stable under recommended storage conditions.
HAZARDOUS CONDITIONS TO AVOID : No decomposition if used according to specifications
INCOMPATIBLE MATERIALS : Keep away from strong acids.
HAZARDOUS DECOMPOSITION PRODUCTS : No dangerous decomposition products known.

SECTION 11 – TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION : **Diethylene Glycol Monobutyl Ether (DB)**
ACUTE TOXICITY : Oral LD50 Oral (rat): 5560 mg/kg. LC50 dermal and inhalation: Not listed.
CHRONIC EFFECTS : Prolonged absorption causes liver and kidney damage, and red cell haemolysis (blood in urine) in laboratory animals; no such effects have been seen in humans
SENSITISATION : Not a sensitizer.
CARCINOGENICITY : No component of this product present at levels greater than or equal to 0.1% is identified as probable or confirmed human carcinogen by IARC, ACGIH, NTP, and OSHA.

TOXICOLOGICAL INFORMATION : **Ethoxylated Alcohol**
ACUTE TOXICITY : LD50 Oral (rat): 1,378 mg/kg,
INHALATION LC50 : No data available.
DERMAL LD50 : LD50 Dermal (rat): > 5,000 mg/kg.
PRIMARY SKIN IRRITATION : (Rabbit) Moderate to severely irritating.
PRIMARY EYE IRRITATION : (Rabbit) Severely irritating.

TOXICOLOGICAL INFORMATION : **Sodium Octane Sulfonate**
ACUTE TOXICITY IRRITATION : Inhalation may cause pain in respiratory system, sneezing coughing and difficulty in breathing.
INHALATION :
CARCINOGENICITY : This product is not considered to be a carcinogen by IARC, ACGIH, NTP or OSHA.

TOXICOLOGICAL INFORMATION : **Sodium Thiosulfate**
ACUTE TOXICITY : LD50: Not available. May cause irritation to Eyes, skin and Respiratory tract.
CARCINOGENICITY : This product is not considered to be a carcinogen by IARC, ACGIH, NTP or OSHA.
MUTAGENICITY : No data available.
SENSITISATION : Not a sensitizer.

SECTION 12 – ECOLOGICAL INFORMATION

SAFETY DATA SHEET

FABRIC MASTER HD

ECOLOGICAL INFORMATION : **Diethylene Glycol Monobutyl Ether (DB)**
ECOTOXICITY : This product cannot accumulate in living tissue; diluted, this product is readily and rapidly in a wastewater treatment facility; in BOD test, 88% degraded in 28 says; half-life in air estimated as 10 hours.

PERSISTENCE AND DEGRADABILITY : No data available.

ECOLOGICAL INFORMATION : **Ethoylated Alcohol**
ECOTOXICITY : LC50 Rainbow Trout: 1-10 mg/l, 96hr. Value estimated from tests on similar products.
LC50 Fathead Minow: 6 mg/l, 96hr. Value estimated from tests on similar products.

BIODEGRADABILITY : Readily biodegradable.

PERSISTENCE AND DEGRADABILITY : No data available.

BIOACCUMULATIVE POTENTIAL : No data available.

ECOLOGICAL INFORMATION : **Sodium Octane Sulfonate**
ACUTE TOXICITY FISH, DAPHNIA, BACTERIA : No ecological data available for this material.

ECOLOGICAL INFORMATION : **Sodium Thiosulfate**

ECOTOXICITY : No data available.

PERSISTENCE AND DEGRADABILITY : No data available.

MOBILITY : No data available.

SECTION 13 – DISPOSAL CONSIDERATIONS

WASTE DISPOSAL : This product must be disposed of in accordance with Federal, state and local environmental regulations. Discarded materials may be considered hazardous waste due to pH/corrosivity. It is the responsibility of the product user to determine at the time of disposal whether a material containing, or derived from this product, should be classified as a hazardous waste.

SECTION 14 – TRANSPORTATION INFORMATION

DOT/IMDG/ IATA PROPER SHIPPING NAME : Not Hazardous

HAZARD CLASS AND LABEL : Not Applicable.

UN NUMBER : Not Applicable.

PACKAGING GROUP : Not Applicable.

EPA REPORTABLE QUANTITY (RQ) : Not Applicable.

MARINE POLLUTANT : Not listed.

EMERGENCY RESPONSE GUIDE : Not Applicable.

SECTION 15 – REGULATORY INFORMATION

U.N. GHS CLASSIFICATION & LABELING INFORMATION: See Section 2 for GHS Hazard Information

U.S. FEDERAL REGULATORY INFORMATION:

LISTED CARCINOGEN : Not listed.

TSCA STATUS : The ingredients of this product are listed in TSCA inventory (40CFR 710.)

SARA SECTION 302 : No chemicals in this material are subject to the reporting requirements of SARA Title

SAFETY DATA SHEET

FABRIC MASTER HD

III, Section 302.
SARA SECTION 312 : Chronic health hazard (Glycol Ether DPM).
SARA SECTION 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.
NFPA HEALTH : 2
NFPA FLAMMABILITY : 0
NFPA REACTIVITY : 0

EUROPEAN UNION REGULATORY INFORMATION:

EC CLASSIFICATION : Xi: Irritant
DSD/DPD RISK (R) PHRASES : R22: Harmful if swallowed.
R36/38: Irritating to eyes and skin.
DSD/DPD SAFETY (S) PHRASES : S1/2: Keep locked up and out of reach of children.
S24/25: Avoid contact with eyes and skin.
S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S36/S37/39: Wear suitable protective clothing, gloves and eye/face protection.
S45: In case of accidents or if you feel unwell, seek medical advice immediately. Show label where possible.
S61: Avoid release to the environment.
S62: If swallowed, do not induce vomiting.
S64: If swallowed, rinse mouth with water if victim is conscious.
DSD/DPD HAZARD SYMBOL : Xi: Irritant



CANADIAN REGULATORY INFORMATION:

WHMIS CATEGORY : D2B: Materials that cause other toxic effects (TOXIC).
DOMESTIC SUBSTANCES LIST (DSL) : Listed
INGREDIENT DISCLOSURE LIST : Listed



SECTION 16 – OTHER INFORMATION

DISCLAIMER : The information contained herein has been compiled from sources believed to be reliable and accurate to the best of our knowledge at this date. It is provided without warranty, expressed or implied, as to the results of use of this information or to the product to which it relates. Wesmar Co. assumes no responsibility for injury to any person or property resulting from any use of the material. Each user assumes the risk in their use of this product and should review the data and recommendations in the specific context of their intended use.

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act.
EINECS : European Inventory of Existing Commercial Chemical Substances
IMDG : International Maritime Code for Dangerous Goods
IARC : International Agency for Research on Cancer
IATA : International Air Transportation Association
ACGIH : American Conference of Governmental Industrial Hygienists
NFPA : National Fire Protection Association (USA)
NTP : National Toxicology Program
SARA : Superfund Amendments and Reauthorization Act
TSCA : Toxic Substances Control Act
HMIS : Hazardous Materials Identification System (USA)

SAFETY DATA SHEET FABRIC MASTER HD

WHMIS : Workplace Hazardous Materials Information System
LC50 : Lethal concentration, 50 percent
LD50 : Lethal dose, 50 percent
STOT : Systemic Target Organ Toxicity
DATE PREPARED : MAR 1, 2012
DATE REVISED : MAR 29, 2018