

# Meet Big Brother

## Key Features

- **38HP KOHLER Command Pro EFI Air Cooled Engine.** EFI Fuel Delivery, EPA approved delivers maximum power and cost efficient performance
- **GD408 Rotary TRI-LOBE Vacuum Blower** produces 500+ CFM of airflow for faster drying, longer hose runs
- **Tri-3VX Belt Drive Power Delivery System** allows for reduced space usage, gearing up power through pulleys and adsorbs mechanical vibration and takes up misalignments. Removable belts make for easy access maintenance
- **Proven MAX-TEMP Heat Exchanger** fin and tube heat exchanger with heat-boost for faster warm-up open design maintaining cleaning solution temperature up to 245°F at intermittent carpet cleaning solution flow rate and 180°F at continuous high pressure solution flow rate
- **Streamlined design and function for clean and simple design.** Belt driven, no diverter valve and minimized wiring
- **Dual wand plumbed** to double your productivity, massive vacuum performance to extend your cleaning reach and maximum productivity every day. Up to 1200 psi.
- **Tough as nails TITAN quality** with more intuitive and easier to use panel directions and graphics for easier operation and maintenance



**Performance that makes you want to get up and go to work every morning**

**Streamlined design and function that increases reliability and makes your work-day simpler!**

# TITAN TOUGH



## TITAN 625



### Applications:

- Dual Wand Cleaning
- Residential and Commercial Carpet Cleaning
- Pressure Washing with full waste recovery capabilities
- Upholstery Cleaning
- Concrete, Stone, Tile and Grout Cleaning
- Water Extraction



**Made in the USA**

**HydraMaster**  
We've Got Your Back

sales@hydramaster.com | 800.426.1301 | 425.775.7272 | www.hydramaster.com



# TITAN 625



**Performance that makes you want to get up and go to work every morning...**  
**Streamlined design and function that increases reliability and makes your work-day simpler!**



## Standard Equipment

- Runtime hour meter
- Chemical flow meter (0-10 GPH)
- Chemical flow control valve
- 5 gallon chemical jug
- Vacuum gauge (0-30" Hg)
- Solution pressure gauge (0-1,200 PSI) Heated
- Solution pressure adjustment
- Pre-wired pump-in switch
- Pre-wired AWDS Switch
- Fresh water inlet
- Water system drain valve
- 1.5 Inch EVOLUTION Wand
- Clutch package for flood work
- Electrical circuit protection
- Pump clutch switch
- Solution temperature control selector
- Two solution outlets
- Solution Hose Length: 100 ft x 1/4"
- Vacuum Hose Length: 100 ft x 2"
- Wand Whip Line: 10 ft x 1-1/2"
- 50 ft water supply line
- Recovery Tank: 70 gallon MaxxAir™
- Battery box
- Van installation kit
- Operation & maintenance manual
- Embroidered HydraMaster jacket

## Optional Accessories

- 100 Gallon Maxx-Air Recovery Tank Upgrade
- AWDS – Automatic Wastewater Disposal System
- RX20 NEXTGEN Rotary Jet Extraction Wand
- DriMaster 3 Upholstery Tool
- EVOLUTION 2" Wand
- EVOLUTION Stair Wand
- EVOLUTION Flood Extraction Wand
- EVOLUTION GLIDED Upholstery Tool
- HydraTank 110G Gallon Submount Freshwater Tank
- 85 Gallon Submount Freshwater Tank
- Through Floor Exhaust Kit
- HydraCradle Freshwater Tank/Hose Reel Combo
- 200-300' Capacity Hose Reels manual and electric
- RX-15H Rotary Hard Surface Tool

## 38HP KOHLER Command Pro EFI Air-Cooled Engine

- Electronic Fuel Injection
- Fully integrated oil cooler extends engine life
- Robust torque output for most demanding applications
- Hydraulic lifters mean zero maintenance on the valve train
- Advanced sensor technology allows engine to optimize performance by automatically adapting to operating conditions
- Fuel consumption –1.6 gph
- Fully sealed inlet duct



## GD 408 Rotary Tri-Lobe Blower

- Quieter operation 3 lobe impeller allows through input while creating lower noise, vibration, and pulsation levels
- Heavy duty industrial design for reduced downtime
  - Dual splash lubrication for longer life and reducing service intervals
  - High strength timing gears for longer service life
  - Piston ring and shaft lip seals prevent oil leakage
  - Large cylinder fins for greater heat dissipation
- Cast aluminum inlet adapters on blower and waste tank to reduce corrosion
- Operates at 3300 RPM
- Up to 510 CFM




## General HTX-1813 High Pressure Solution Pump

- 4.0 gpm volume/Up to 1200 psi.
- Triplex plunger pump
- Features patented "high tech" packings
- Patented inlet/outlet valve cage
- Nickel-plated inlet/outlet valve plugs
- Nickel-plated forged brass manifold with exclusive lifetime warranty
- Specially designed to handle rigorous duty cycles, high temperatures and chemicals
- Chemical System – last-step chemical injection and meter controlled



## MAX-TEMP Thermal Capture and Heat Exchange System

- Tube and Fin heat exchanger with heat-boost for faster warm-up
- Attains and maintains cleaning solution temperature up to 245°F at intermittent carpet cleaning solution flow rate and 180°F at continuous high pressure solution flow rate
- Easy to access and remove core for easy cleaning and maintenance



Made in the USA

## Machine Specifications

- Dimensions: 26"W x 45"D x 39"H
- Console weight: 850 lbs

**HydraMaster**  
We've Got Your Back

www.hydrmaster.com | 800.426.1301 | 425.775.7272